



Collamat® Top and bottom labelling solutions
Labelling Your Product - Our Competence.

Collamat® Top and bottom labelling solutions

Highly Flexible Collamat® Standard Solution to underline our slogan:
Labelling Your Product – Our Competence

Standard system advantages:

- Space saving and compact unit
- Robust design
- Easy installation-plug and play
- Easy to operate
- Durable



Choose the solution which fits your product and production and you are ready to start labelling in a short time.



TECHNICAL DATA	
System	Stainless steel base Conveyor Control box
Belt height	900 mm (2'11") Adjustable +/-50 mm (+/- 2")
Belt length	Standard: 1.200 mm (3'11") Options: 1.500 mm (4'11") or 2.000 mm (6'7")
Belt width	Standard: 120 mm (4 3/4") Options: 200 mm for wide edge labellers (7 7/8")
Belt speed	1. 3-20 m/min variable speed (9.8-65.6 ft/min) 2. 20-50 m/min variable speed (65.6-164 ft/min)
Operational width	Standard: 95 mm (3 3/4") Option: 160 mm (not possible for C 2610) (6 1/4")
Max. speed	Collamat® C 2610* - 15 m/min (49 ft/min) Collamat® C 4300* - 25 m/min (82 ft/min) Collamat® C 7300* - 50 m/min (164 ft/min) Collamat® S 50* - 50 m/min (164 ft/min)
Printing & Labelling	Collamat® Etiprint Inline 30* - 30 m/min (98 ft)
Technical requirements	Electric power 110/230 V
*See the technical specifications for detailed product information	

Collamat®

Hofackerstrasse 73, CH-4132 Muttenz, Switzerland
Tel.: +41 61 756 28 28, Fax: +41 61 756 29 29
contact@collamat.ch, www.collamat.ch

Swiss Modular Labellers 